



No	L	CABLE
DW-F5E-0025-GR	250 ± 40mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-005-GR	500 ± 40mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-010-GR	1000 ± 40mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-020-GR	2000 ± 40mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-030-GR	3000 ± 40mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-050-GR	5000 ± 100mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-070-GR	7000 ± 100mm	CAT. 5E/FTP 26AWG, GREY
DW-F5E-100-GR	10000 ± 100mm	CAT. 5E/FTP 26AWG, GREY

NOTES:

- ELECTRICAL TEST:100% OPEN, SHORT & MISS WIRE TEST.
- CONDUCTOR RESISTANCE:10 OHMS MAX.
- INSULATOR RESISTANCE:5M OHMS MIN, DC 300V 0.01sec.
- HI-POT: DC 300V 0.1sec.

3	Cable	CAT. 5E/FTP CABLE 26AWG(7/0.16)*4P+AL+D(7/0.12BS) JACKET: PVC, GREY; OD:5.5 ± 0.2mm	1
2	Molding	45P PVC OUTER MOLDING HOUSING, COLOR:GREY	2
1	Connector	RJ45 MALE CONNECTOR (SHIELD), PIN GOLD PLATED 3U".	2
NO	PART NAME	DESCRIPTION	QTY

-TOLERANCES- UNLESS OTHERWISE SPECIFIED					
UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 - 8mm ± 0.20mm 8 - 30mm ± 0.25mm 30 - 120mm ± 0.30mm	Appd: JIM KING		PART DESCRIPTION: Patch Cable CAT5E FTP PVC 5m Gray Non-Snag-Proof		
	Check:	Date	Scale	Unit	Type
Draw: Gavin	2022.11.30	Free	MM	Z	1/1