



<b>Symbol:</b>	AX-MS8221B
<b>Skupina výrobků:</b>	Digital Multimeters

## Parametry výrobku

<b>Type of meter:</b>	digital multimeter
<b>Measurement:</b>	AC current, AC voltage, DC current, DC voltage, resistance
<b>Kind of display used:</b>	LCD
<b>Display parameters:</b>	3,5 digit (1999)
<b>Sampling:</b>	2,5x/s
<b>DC voltage measuring range:</b>	200mV, 2V, 20V, 200V, 600V
<b>DC voltage measuring accuracy:</b>	$\pm(0.5\% + 3 \text{ digit})$
<b>AC voltage measuring range:</b>	2V, 20V, 200V, 600V
<b>AC voltage measuring accuracy:</b>	$\pm(1.2\% + 3 \text{ digit})$
<b>DC current measuring range:</b>	0.2mA, 2mA, 20mA, 200mA, 10A
<b>DC current measuring accuracy:</b>	$\pm(0.8\% + 1 \text{ digit})$
<b>AC current measuring range:</b>	2mA, 20mA, 200mA, 10A

## Karta výrobku AX-MS8221B

<b>AC current measuring accuracy:</b>	±(1.2% + 3 digit)
<b>Resistance measuring range:</b>	200Ω, 2kΩ, 20kΩ, 200kΩ, 2MΩ, 20MΩ
<b>Resistance measuring accuracy:</b>	±(1%+2 digit)
<b>Diode test:</b>	1mA @2.8V
<b>Continuity test:</b>	acoustic indication, <50Ω
<b>Pollution degree:</b>	2
<b>Weight with battery:</b>	250g
<b>Power supply:</b>	battery 6F22 9V x1
<b>Standard equipment:</b>	test leads
<b>Optional equipment:</b>	test leads AX-TL-4B1-B, test leads AX-TL-4B1-BL, test leads AX-TL-4B1-R, test leads AX-TL-BNC-4BP2, test leads AX-TLP-001, test leads AX-TLP-001T, test leads AX-TLP-002, test leads AX-TLP-003, test leads AX-TLS-001B, test leads AX-TLS-002B, test leads AX-TLS-003A, test leads AX-TLS-004A, test leads AX-TLS-005A, test leads AX-TLS-007S, test leads PPOM-14, test tweezers AX-TLP-TW-01
<b>Conform to the norm:</b>	CAT III 600V, EN 61010
<b>Dimensions (W x H x D):</b>	74x158x32mm
<b>Measuring instrument features:</b>	HOLD function, low battery indicator, manual ranging, universal
<b>Battery/rechargeable battery:</b>	battery 6F22 9V x1

**Display height 1:** 15mm

## **Doplňková informace**

**Hmotnost brutto:** 0.2682 kg