

Chateau LTE12

Your best friend when it comes to mobile networks.

Amazing in the hands of seasoned system administrators.

Or in a household with zero IT skills. Or anything in between.

Chateau can do it all.



New modem by Quectel: added 4x4 MIMO for more bands: 1/3/7/38/40/41



5X GIGABIT ETHERNET PORTS



FAST AND RESPONSIVE LTE CATEGORY 12 MODEM



MOBILE CONNECTIONS UP TO 600 MBPS



POWERFUL QUAD-CORE ARM CPU



STRONG DUAL-BAND, DUAL-CHAIN RADIO FOR MAXIMUM COVERAGE



CONTAINER SUPPORT

Remove the bottleneck in your mobile internet setup

Are you tired of ISP or operator-issued routers that limit your speed and coverage? Chateau LTE12 is the solution, delivering faster, more reliable mobile internet, whether you are in the city or the countryside. With carrier aggregation and expanded 4x4 MIMO support, you'll experience:

- Faster speeds in crowded areas
- More stable connections in remote locations
- Wider coverage across multiple LTE band



New and improved LTE connectivity:



Upgraded LTE12 modem

for stronger, reliable connections.

Now with B32 support for improved LTE performance in supported regions!



Expanded 4x4 MIMO support on more bands: 1/3/7/38/40/41



Dual-band Wi-Fi for seamless performance across all devices

Built for homes and businesses

- **5x Gigabit Ethernet ports** to connect media servers, PC towers, TVs, or smart home systems.
- Dual-band Wi-Fi (2.4 GHz & 5 GHz) ensures stable connections for all your devices.
- External LTE antenna support (not included) to boost signal strength in tricky signal areas.
- RouterOS for advanced security, VPNs, and full network control.

Stay ahead of connectivity challenges with the improved Chateau LTE12.

Powerful, secure, and designed to keep you connected—anytime, anywhere!



Specifications

Product code	D53G-5HacD2HnD-TC&EG120K-EA	
CPU	Quad-Core IPQ-4019 448-896 MHz (auto)	
CPU architecture	ARM 32bit	
Size of RAM	256 MB	
RAM type	DDR3L	
Storage	32 MB, Flash	
Number of 1G Ethernet ports	5	
USB port	1 (2.0 type A)	
Switch chip model	IPQ-4019	
Wireless interface model	IPQ-4019 (2.4 GHz), IPQ-4019 (5 GHz)	
Wireless	2.4 GHz 802.11b/g/n dual-chain, 5 GHz 802.11a/n/ac dual-chain	
Antenna gain	2.4 GHz - 2 dBi, 5 GHz - 4 dBi	
LTE category	12 (600Mbps Downlink, 150Mbps Uplink)	
LTE modem	EG120K-EA	
TAC	86056104	
MIMO DL	4x4	
MIMO UL	1x1	
LTE FDD bands	1 (2100MHz) / 3 (1800MHz) / 5 (850MHz) / 7 (2600MHz) / 8 (900 MHz) / 20 (800MHz) / 28 (700MHz) / 32 (1500 MHz)	
LTE TDD bands	38 (2600MHz) / 40 (2300MHz) / 41 (2500MHz)	
3G Category	R8 (42.2Mbps Downlink, 5.76Mbps Uplink)	
3G Bands	1 (2100MHz) / 3 (1800MHz) / 5 (850MHz) / 8 (900MHz)	
Dimensions	240 x 156 x 44 mm	
Operating system	RouterOS v7, License level 4	
Operating temperature	-20°C to +70°C	

Wireless specifications

Rate (2.4 GHz)	Tx (dBm)	Rx (dBm)
1MBit/s	25	-100
11MBit/s	25	-94
6MBit/s	26	-95
54MBit/s	23	-78
MCS0	26	-96
MCS7	22	-73

Rate (5 GHz)	Tx (dBm)	Rx (dBm)
6MBit/s	26	-96
54MBit/s	22	-80
MCS0	26	-96
MCS7	21	-75
MCS9	19	-70

Powering

Number of DC inputs	1
DC jack input Voltage	12-28 V
Power adapter nominal voltage	24 V
Power adapter nominal current	1.2 A
Max power consumption without attachments	18 W
Max power consumption	24 W

Chateau LTE12

Included parts





24 V 1.2 A power adapter

UTP Flat Cable (1.5m)

Chateau LTE12 4